

3x3

AR-AFFF FREEZE PROTECTED

PSEUDOPLASTIC FOAM CONCENTRATE

TYPICAL PHYSICAL PROPERTIES (Concentrate)

Specific gravity @ 68° F (20° C)	1.06
pH	7.5 ± .05
Viscosity	2000 cps
Lowest temperature for use	0° F
Freezing point	~-7° F

TYPICAL PROPERTIES (Solution)

Dilution rate	3%
Surface tension at @ 68° F (20° C)	16.5 ± 0.5
Interfacial tension with cyclohexane at @ 68° F (20° C)	3.2 ± 1.0
25% drain time (minutes)	> 4:50

PACKAGING

ORDERING INFORMATION (LBS./kg.)

	LBS	KG	PRODUCT #
5 gallon pails (19 liters)	44	20	10004064
55 gallon drums (208 liters)	475	221	10004063
265 gallon reusable tote tank (984 liters)	2348	1065	10004062

Approximate weight



DESCRIPTION

Phos-Chek® 3x3 AR-AFFF FP (Alcohol-Resistant Aqueous Film Forming Foam Freeze Protected) is a mixture of water, hydrocarbon surfactants, solvents, C6 fluorosurfactants and fluoropolymers. The product is a 3% concentrate proportioned solution for use on both hydrocarbon and polar solvent fires. This new formulation demonstrates Perimeter Solutions' commitment to superior firefighting performance and environmental responsibility. Phos-Chek 3x3 AR-AFFF FP is designed for rapid control and knockdown by producing a thin aqueous film on hydrocarbon fuels or a polymer membrane on polar solvent fuels that minimize vapor release, a foam blanket that separates the fuel from the air, and continual draining of water from the foam blanket provides cooling at the fuel surface. Phos-Chek 3x3 AR-AFFF FP concentrate is ideal for use on fixed foam systems and manual firefighting operations in low temperature (-7° F or -22° C) areas.



For more information, contact any of our worldwide Perimeter Solutions Fire Safety offices or visit us at www.Phos-Chek.com or Perimeter-Solutions.com

United States

Perimeter Solutions
10667 Jersey Blvd.
Rancho Cucamonga,
CA 91730
Tel: (800) 682-3626
(909) 983-0772
24 Hrs: (909) 946-7371
Fax: (909) 984-4770

Canada

Perimeter Solutions
Canada LTD
3060 Airport Road
Kamloops, BC
Canada, V2B 7X2
Tel: (800) 682-3626
(909) 983-0772
24 Hrs: (909) 946-7371
Fax: (909) 984-4770

Europe

Auxquimia S.A.U.
Poligono Industrial de
Baña, Parc, 23
33682 Baña-Mieres
Asturias - Spain
Tel: +34 985 242945
Fax: +34 985 253809

3x3



AR-AFFF FREEZE PROTECTED

PSEUDOPLASTIC FOAM CONCENTRATE

HANDLING PRECAUTIONS

- FOR DETAILED SAFETY INFORMATION, please refer to the SDS.
- Precautionary Measure and First Aid: Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- Eye Protection: As a good industrial practice, the use of chemical goggles is recommended. If in the eyes, flush immediately with water. Eye flushing equipment should also be available.
- Skin Protection: Wear protective gloves when handling concentrate to minimize skin contact. Wash hands and contaminated skin after handling.
- Respiratory Protection: None required. The location for public viewing of the SDS is on www.phos-chek.com

APPLICATIONS

Phos-Chek 3x3 AR-AFFF FP is used in fire suppression systems and manual applications to fight a broad range of Class B flammable liquid fires including hydrocarbon fuels such as gasoline and diesel, and on polar solvent fuels such as ketones and alcohols. Typical applications include storage tanks, loading racks, docks, process areas, warehouses, and is an excellent vapor suppressor for flammable liquid spills.

SHELF LIFE, INSPECTION AND TESTING

The shelf life of any foam concentrate is maximized by The shelf life of any foam concentrate is maximized by proper storage conditions and maintenance. Factors affecting shelf life are wide temperature changes, extreme high or low temperatures, evaporation, dilution, and contamination by foreign materials. Properly stored Phos-Chek AR-AFFF Class B foam concentrates should have no significant loss of firefighting performance for 20+ years. However, the National Fire Protection Association (NFPA) recommends annual testing of all firefighting foams.

STORAGE AND HANDLING

The concentrate should be stored at temperatures between 0°F (-17°C) and 122°F (+50°C), preferably in the original containers, approved bladder tanks, stainless steel, high density polyethylene, fiberglass or epoxy lined tanks. Concentrate piping acceptable materials of construction include stainless steel (either 304 or 316), some plastic piping including fiberglass and PVC, red brass, and black iron as long as the system is completely flooded eliminating the air/foam concentrate/carbon steel interface. Avoid permanent contact with carbon steel, iron, some copper alloys, & aluminum when the piping material and concentrate will be exposed to air. Galvanized piping is not recommended for AFFF piping systems. Foam concentrates are subject to evaporation, which accelerates when the product is exposed to air. Storage tanks should be sealed and fitted with a pressure vacuum vent to prevent free exchange of air.

NOTICE

Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, Perimeter Solutions LP and its affiliates makes no representations or warranties as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Perimeter Solutions LP be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information or the product to which the information refers. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent, and Perimeter Solutions LP makes no representation or warranty, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

© 2018 Perimeter Solutions LP. All rights reserved.



APPROVAL CERTIFICATIONS
UL 162, EN 1568-3 (Class IA)
and EN 1568-4 (Class IB)